



Radiator Anti-Rust Additive and Water Pump Lubricant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/31/2017

Revision date: 08/31/2018

Supersedes: 07/02/2018

Version: 1.2

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : Radiator Anti-Rust Additive and Water Pump Lubricant
Product code : 8117

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Radiator additive

1.3. Supplier

Bardahl Manufacturing Corporation
1400 NW 52nd Street
P.O. Box 70607
Seattle, WA 98107
T 206-783-4851 - F 206-784-3219
jackie.leung@bardahl.com - www.bardahl.com

1.4. Emergency telephone number

Emergency number : 800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral), Category 4	Harmful if swallowed.
Acute toxicity (dermal), Category 3	Toxic in contact with skin.
Skin corrosion/irritation, Category 2	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	Causes serious eye irritation.
Hazardous to the aquatic environment — Acute Hazard, Category 3	Harmful to aquatic life

2.2. GHS Label elements, including precautionary statements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Harmful if swallowed.
Toxic in contact with skin.
Causes skin irritation.
Causes serious eye irritation.
Harmful to aquatic life

Precautionary statements (GHS-US) :

Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.
Avoid release to the environment.
Wear eye protection, protective clothing, protective gloves.
If swallowed: Call a POISON CENTER if you feel unwell
If on skin: Wash with plenty of water
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a doctor if you feel unwell
Rinse mouth.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off immediately all contaminated clothing and wash it before reuse.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

Radiator Anti-Rust Additive and Water Pump Lubricant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Morpholine	(CAS-No.) 110-91-8	1 - 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

Radiator Anti-Rust Additive and Water Pump Lubricant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Radiator Anti-Rust Additive and Water Pump Lubricant		
ACGIH	ACGIH TWA (ppm)	20 ppm Morpholine
ACGIH	ACGIH STEL (ppm)	20 ppm Morpholine
OSHA	OSHA PEL (TWA) (ppm)	20 Morpholine
Morpholine (110-91-8)		
ACGIH	Local name	Morpholine
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye dam; URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	70 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	20 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Protective clothing. Gloves. Safety glasses.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke when using this product.

Radiator Anti-Rust Additive and Water Pump Lubricant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: clear
Odour	: mild
Odour threshold	: No data available
pH	: 11 - 11.6
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 °C approximately
Flash point	: > 100 °C greater than
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.02
Solubility	: Soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Oral: Harmful if swallowed.
Acute toxicity (dermal)	: Dermal: Toxic in contact with skin.
Acute toxicity (inhalation)	: Not classified

Radiator Anti-Rust Additive and Water Pump Lubricant

LD50 oral rat	1450 mg/kg Morpholine
LD50 dermal rabbit	500 mg/kg Morpholine

Radiator Anti-Rust Additive and Water Pump Lubricant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Radiator Anti-Rust Additive and Water Pump Lubricant	
LC50 inhalation rat (ppm)	4000 ppm/4h Morpholine
ATE US (oral)	1450 mg/kg bodyweight
ATE US (dermal)	500 mg/kg bodyweight
ATE US (gases)	4000 ppmv/4h

Morpholine (110-91-8)	
LD50 oral rat	1900 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	500 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (oral)	1900 mg/kg bodyweight
ATE US (dermal)	500 mg/kg bodyweight
ATE US (gases)	4500 ppmv/4h
ATE US (vapours)	11 mg/l/4h
ATE US (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: 11 - 11.6
Serious eye damage/irritation	: Causes serious eye irritation. pH: 11 - 11.6
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

Radiator Anti-Rust Additive and Water Pump Lubricant	
LC50 fish 1	180 - 380 mg/l 96 hr - Oncorhynchus mykiss (rainbow trout)
EC50 Daphnia 1	100 mg/l 24 hr - Daphnia magna (Water flea)
EC50 other aquatic organisms 1	> 310 mg/l 72 hr - Desmodesmus subspicatus (green algae)
EC50 other aquatic organisms 2	> mg/l
LOEC (acute)	80 mg/l 72 hr - Desmodesmus subspicatus (green algae)

Morpholine (110-91-8)	
LC50 fish 1	180 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	45 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, Locomotor effect)

12.2. Persistence and degradability

Radiator Anti-Rust Additive and Water Pump Lubricant	
Persistence and degradability	Readily biodegradable in water.

Morpholine (110-91-8)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.02 g O ₂ /g substance
ThOD	2.6 g O ₂ /g substance

Radiator Anti-Rust Additive and Water Pump Lubricant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

Morpholine (110-91-8)	
BCF fish 1	< 2.8 (Equivalent or similar to OECD 305, 6 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value)
Log Pow	-2.55 - -0.84 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Morpholine (110-91-8)	
Surface tension	0.0375 N/m
Log Koc	0.867 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Morpholine (110-91-8)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

Radiator Anti-Rust Additive and Water Pump Lubricant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Morpholine(110-91-8)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 08/31/2018


Full text of H-statements:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H332	Harmful if inhaled.
H402	Harmful to aquatic life

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : C
C - Safety glasses, Gloves, Synthetic apron

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product