



# XTC 100% SYNTHETIC 5W-20

ILSAC GF-5, API SN, SN-RC 22900

TECH REPORT

## Product Description

**XTC 100% SYNTHETIC 5W-20 PASSENGER CARE ENGINE OIL** is a high performance synthetic oil designed to meet the latest car manufacturers warranty requirements. Specifically formulated to meet the demands of the small displacement high RPM fuel efficient engines found in today's domestic and foreign automobiles.

The oil is 100% synthetic of the highest quality and special additives which protect against high temperature oxidation, wear, and viscosity breakdown. It is fortified with detergent-dispersants, rust, corrosion inhibitors and friction modifiers to keep engines exceptionally clean and free of sludge, varnish, rust and meet the fuel economy requirements.

## Advantages & Uses

- XTC 100% SYNTHETIC 5W-20 meets or exceeds ILSAC GF-5 and API Service Classification of SN and SN-RC requirements and is recommended for domestic and foreign high performance engines. It is recommended for small, high RPM engines including those that are turbo charged.
- Recommended for passenger cars, light duty pickups, motorcycles and other gasoline engines in mobile and stationary service.
- Appropriate viscosity grades meet the warranty requirements of Chrysler (MS 63955), Ford Motor Co. (WSS-M2C946A), and General Motors specification of GMW-16181.



## Features

- XTC 100% SYNTHETIC 5W-20 meets or exceeds OEMs warranty requirements.
- Highly oxidation stable – protects engine from oil thickening, high temperature sludge and varnish deposits.
- Shear stable viscosity index improver – protects against viscosity breakdown in severe service.
- Effective detergent-dispersants keep engine parts clean.
- Improved fuel economy means better gasoline mileage.
- High TBN / alkaline reserve effectively neutralizes corrosive acids formed by combustion to protect critical turbo charger bearings and other vital engine surfaces.
- Anti-wear agents effectively protect cam lobes and other highly loaded parts from wear.

Test	ASTM	5W-20
Gravity, °API	D-287	32.5
Flash Point, °C	D-92	229
Pour Point, °C	D-97	-39
Viscosity @ 100°C, Cst	D-445	8.5
Viscosity @ -15°C, CCS	D-5293	5,100
Viscosity Index	D-2270	155
Appearance	Visual	Bright & Clear
Color	D-1500	Amber
Zinc, wt %		0.085
Phos,Wt %		0.077
TBN	D-2896	97.9

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

